

# Grease Guns 1077600 and TLGH 1

## Easy grease filling

The SKF Grease Guns are ideal for agricultural, industrial and construction industries and for private use. The SKF Grease Guns are delivered with a 175 mm (6.9 in) long extension pipe with hydraulic gripping nozzle. A flexible 500 mm (19.7 in) long pressure hose with hydraulic gripping nozzle is available as an accessory.

- For use with cartridges and loose grease
  - Knurled body for firm and safe grip
  - High quality steel is dent-resistant for easy cartridge loading
  - Special piston design for smooth emptying of cartridges
  - 40 MPa (5,800 psi) maximum pressure
  - 1077600: 1,5 cm<sup>3</sup> (0.092 in<sup>3</sup>) volume/stroke
  - TLGH 1: 0.9 cm<sup>3</sup> (0.055 in<sup>3</sup>) volume/stroke
- The 1077600 is also available with a with 300 mm (12 inch) high pressure hose with a hydraulic gripping nozzle, 1077600H



The 1077600 is also available as a complete set; 1077600/SET including 3 extension pipes, high pressure hose, packed in a carrying case.

### TLGH 1

Designation	TLGH 1
Maximum pressure	40 MPa (5,800 psi)
Volume/stroke	Approx. 0,9 cm <sup>3</sup> (0.05 in <sup>3</sup> )
Length	380 mm (15 in)
Weight	1,5 kg (3.3 lb)

### 1077600

Designation	1077600
Maximum pressure	40 MPa (5,800 psi)
Volume/stroke	1,5 cm <sup>3</sup> (0.09 in <sup>3</sup> )
Length	380 mm (14.9 in)
Weight	1,5 kg (3.3 lb)

# One Hand Operated Grease Gun LAGH 400

## Easy grease filling with one hand

Suitable for grease filling by grease filler pumps and also suitable for grease cartridges. Ergonomic design, flexible hose and possibility to mount the hose in both vertical and horizontal position make it easy to use.

- Easy-to-use: only one hand is needed to operate the gun
- Refillable: grease filling nipple and de-airing valve allow filling up by filler or grease pump
- Heavy duty: operating pressure up to 30 MPa
- 0,8 cm<sup>3</sup> (0,05 in<sup>3</sup>) volume/stroke
- Flexible hydraulic type hose: can be bent, can be mounted both horizontally and vertically on the gun



### Technical data

Designation	LAGH 400	Length	370 mm (14.6 in)
Maximum pressure	30 MPa (4 350 psi)	Weight	1,5 kg (3.3 lb)
Volume/stroke	approx. 0,8 cm <sup>3</sup> (0.049 in <sup>3</sup> )		



Re-lubrication



# Grease Packer LAGP 400

## To lubricate open bearings

The grease packer LAGP 400 is a low-pressure alternative for emptying SKF grease cartridges. It provides an easy and clean alternative to manual grease packing of open bearings.

- Supplied with three spout caps
- Applies grease to open applications such as bearings or open gears



### Technical data

Designation	LAGP 400		
Maximum volume per stroke	20 cm <sup>3</sup> (1.2 in <sup>3</sup> )	Length	360 mm (14 in)
Material	steel and polyethylene	Weight	0,35 kg (0.77 lb)

# Bearing Packer VKN 550

## Contamination free grease filling

The SKF Bearing Packer, VKN 550, is a sturdy, easy-to-use, efficient and effective bearing grease packer. It can also be used in combination with a standard grease gun, air-operated grease pump or grease filler pump. Although specially designed for taper roller bearings, the SKF Bearing Packer works for any type of open bearing which needs to be 100% pre-filled with grease.

- Flushes the grease between the rolling elements where it matters most, prolonging the bearing service life
- Closed system and the cover lid prevent ingress of dirt virtually eliminating contamination
- Allows the operator to pre-fill bearings with grease in a quick and clean way
- Prevents unnecessary grease loss
- Economical and environmentally friendly



### VKN 550

Designation	VKN 550		
Description	Bearing grease packer	Other greases	NLGI class 000 to 2
Weight	1,8 kg (3.9 lb)	Bearing range	19 to 120 mm
Material	Zinc plated, metal finish	– Inner diameter d	Max 200 mm
Suitable greases	approved for all SKF greases	– Outer diameter D	

© SKF is a registered trademark of the SKF Group  
© SKF Group 2009

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

MP/PDS 1077600 EN • October 2009

[www.mapro.skf.com](http://www.mapro.skf.com) • [skf.com/mount](http://skf.com/mount) • [skf.com/lubrication](http://skf.com/lubrication)

