

LGWA 2

SKF high load, extreme pressure, wide temperature range bearing grease

LGWA 2 is premium quality mineral oil based lithium complex grease with extreme pressure (EP) performance. LGWA 2 has such properties that it can be recommended for a wide range of industrial and automotive applications.

- Excellent lubrication at peak temperatures up to 220 °C (428 °F) for short periods
- Protection of wheel bearings operating under severe conditions
- Effective lubrication in wet conditions
- Good water and corrosion resistance
- Excellent lubrication under high loads and low speeds

Typical applications:

- Wheel bearings in cars, trailers and trucks
- Washing machines
- Electric motors

Bearing operating conditions

Temperature	Medium to high
Speed	Low to medium
Load	High
Vertical shaft	○
Fast outer ring rotation	○
Oscillating movements	○
Severe vibrations	○
Shock load or frequent start-up	+
Low noise	—
Low friction	○
Rust inhibiting properties	+
+ = Recommended ○ = Suitable — = Not suitable	

Available pack sizes LGWA 2

SYSTEM 24	35 g tube	200 g tube
420 ml cartridge	1 kg can	5 kg can
50 kg drum	180 kg drum	



Re-lubrication



Technical data

Designations	LGWA 2		
DIN 51825 code	KP2N-30	Water resistance	
NLGI consistency class	2	DIN 51 807/1, 3 hrs at 90 °C	1 max.
Soap type	Lithium complex	Oil separation	
Colour	Amber	DIN 51 817, 7 days at 40 °C, static, %	1 - 5
Base oil type	Mineral ester	Lubrication ability	
Operating temperature range, °C (°F)	-30 to 140 (-22 to 284)	SKF R2F, running test B	Pass at 100 °C (212 °F)
Dropping point DIN ISO 2176, °C (°F)	> 250 (482)	Copper corrosion	
Base oil viscosity:		DIN 51 811, 100 °C	2 max. (150 °C/300 °F)
40 °C, mm ² /s	185	Rolling bearing grease life	
100 °C, mm ² /s	15	SKF R0F test L50 life at 10 000 rpm, hrs	-
Penetration DIN ISO 2137:		EP performance	
60 strokes, 10 ⁻¹ mm	265 - 295	Wear scar DIN 51350/5, 1 400 N, mm	1,6 max.
100 000 strokes, 10 ⁻¹ mm	+50 max. (325 max.)	4-ball test, welding load DIN 51350/4	2 600 N min.
Mechanical stability:		Fretting corrosion	
Roll stability, 50 hrs at 80 °C, 10 ⁻¹ mm	+50 max. change	ASTM D4170 (mg)	
Roll stability, 72 hrs at 100 °C, 10 ⁻¹ mm	-	Designation	LGWA 2/(pack size)
SKF V2F test	'M'		
Corrosion protection:		<i>* Typical value</i>	
SKF Emcor			
- standard ISO 11007	0 - 0		
- water washout test	0 - 0		
- salt water test (100% seawater)	-		

© SKF is a registered trademark of the SKF Group
 © SKF Group 2009

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

MP/PDS LGWA2 EN • October 2009

www.mapro.skf.com • skf.com/lubrication

